AMENDMENTS TO THE CLAIMS

- 1. (Currently Amended) A method of decomposing an image comprising the steps of:
 - a) decomposing the image into a plurality of stripes;
- b) decomposing each stripe into foreground and background image layers, and a mask layer; and determining a layer base color, a layer size and a layer offset of at least one stripe of the plurality of stripes;
- c) separating said at least one stripe into a foreground layer, a background layer and a mask layer based on the layer base color and the layer offset; and
- <u>d)</u> interpolating irrelevant pixel values in the foreground <u>layer</u> and background <u>layers layer</u> for coder efficiency.
- 2. (Currently Amended) The method of claim 1 further comprising the step of:
- d) e) encoding the foreground <u>layer</u>, background <u>layer</u>, and mask layers <u>layer</u>.
- 3. (Currently Amended) The method of claim 2 wherein the foreground <u>layer</u> and background <u>layer</u> are JPEG encoded, wherein the mask <u>layer</u> is JBIG encoded.

Serial No.: 10/036,979

10006292-1/JPW/MJB

Examiner: Larose, Colin M. Art Unit: 2623

- 2 -

- 4. (Currently Amended) The method of claim 1 wherein step c) step d) further comprises the steps of:
- i) determining [a] the layer base color and offsets the layer offset to a common reduced area of each at least one layer to identify image and mask layer values for all regions except an overlapped common reduced area; and
- ii) separating the overlapped common reduced area into <u>a</u> foreground <u>layer</u> and <u>a</u> background <u>layers layer</u>.
- 5. (Currently Amended) The method of claim 1 wherein step c) step d) further comprises the steps:
- i) classifying each <u>at least one</u> pixel within a selected block of a selected layer as relevant or irrelevant;
- ii) generating a coefficient block representing a forward transform of the selected block; and
- iii) modifying coefficient values to generate a modified coefficient block subject to a set of pre-determined constraints including a constraint that the relevant pixels have a same value in an inverse transformation of the modified coefficient block as in the selected block.
- 6. (Original) The method of claim 5 wherein step c)iii) step d)iii) includes the steps of:
- a) selecting a coefficient from the coefficient block in a reverse zigzag order wherein the selected coefficient has a non-zero value; and

Serial No.: 10/036,979 Examiner: Larose, Colin M.

10006292-1/JPW/MJB - 3 - Art Unit: 2623

- b) finding a feasible solution resulting in a zero quantizable selected coefficient subject to the pre-determined constraints.
- 7. (Original) The method of claim 5 wherein the coefficient values are modified subject to a constraint that no zero quantizable coefficient preceding the selected coefficient in the reverse zig-zag order is permitted to become non-zero quantizable.
- 8. (Original) The method of claim 5 wherein values of individual elements of a mask classify pixels in corresponding positions within the selected block as relevant or irrelevant.
- 9. (Currently Amended) The method of claim 5 further comprising the step of:
- d) e) providing the modified coefficient block to a block compression process.
- 10. (Original) The method of claim 5 wherein step c) step d) further comprises the step of applying a linear program to identify a feasible solution resulting in a zero-quantizable coefficient subject to the constraints.

Serial No.: 10/036,979

10006292-1/JPW/MJB

Examiner: Larose, Colin M. Art Unit: 2623

- 11. (Original) The method of claim 10 further comprising the step of applying a quadratic program to generate a modified selected block having minimal energy.
- (Original) The method of claim 10 further comprising the step of 12. terminating further modifications to the coefficient block if a ratio of the energy of the modified block to the energy of the initial selected block exceeds a predetermined threshold.
- (Original) The method of claim 5 wherein the forward transform is 13. one of a discrete cosine, a discrete sine, and a discrete Fourier transform.
- 14. (Currently Amended) A method of decomposing an image comprising the steps of:
 - decomposing the image into a plurality of stripes; a)
- decomposing each at least one stripe into foreground and b) background image layers, and a mask layer;
- identifying an area of intersection of a common reduced c) foreground area and a common reduced background areas, wherein the identifying further comprises:
 - computing a maximum block range for a selected block of the area of intersection; and

Serial No.: 10/036,979 Examiner: Larose, Colin M. Art Unit: 2623 10006292-1/JPW/MJB

- of the foreground and background planes in accordance with whether
 the average luminance of the selected block is closer to a previous
 average foreground luminance or previous average background
 luminance, respectively, if the maximum block range is not greater than
 a pre-determined threshold; and
- d) interpolating any irrelevant pixel values within the area of intersection for coder efficiency for each at least one layer.
- 15. (Original) The method of claim 14, wherein the area of intersection is selected to have an edge that is 8N pixels from at least one of an edge of the common reduced foreground area and the common reduced background area, wherein N is an integer, wherein N≥0.
- 16. (Currently Amended) The method of claim 14, wherein step d) further comprises the steps of:
 - i) selecting a block of pixels; and
- ii) classifying each at least one pixel with the selected block as irrelevant or relevant.
- 17. (Currently Amended) The method of claim 16 further comprises the steps of:

Serial No.: 10/036,979 Examiner: Larose, Colin M.

10006292-1/JPW/MJB - 6 - Art Unit: 2623

- iii) calculating an average value of any at least one relevant pixels pixel within the selected block; and
- assigning the average value to all at least one irrelevant pixels iv) within the selected block.
- 18. (Currently Amended) The method of claim 14, wherein step c) further comprises the steps of:
- computing a maximum block range for a selected block of the i) area of intersection;
- dividing pixels within the selected block into a plurality of groups; ii) and
- assign each at least one selected group to one of the foreground iii) and background planes in accordance with a relative average luminance value of the selected group and another group, if the maximum block range exceeds a pre-determined threshold.
- 19. (Original) The method of claim 18, wherein step c)iii) further comprises the step of assigning the selected group to the background layer and the other group to the foreground layer if an average luminance of the selected group is greater than an average luminance of the other group, wherein the selected group is assigned to the foreground layer and the other group to the background layer if the average luminance of the selected group is not greater than the average luminance of the other group.

Serial No.: 10/036,979

10006292-1/JPW/MJB

Examiner: Larose, Colin M.

Art Unit: 2623

20. (Cancelled)

Serial No.: 10/036,979 10006292-1/JPW/MJB Examiner: Larose, Colin M. Art Unit: 2623

- 8 -